DEC 18 2006

# IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:

Alan C. Berkema et al.

Examiner: Peter Poltorak

Serial No.:

09/897,656

Group Art Unit: 2134

Filed:

June 29, 2001

Docket No.: 10016784-1

Title:

PORTABLE WIRELESS DEVICE AND SOFTWARE FOR PRINTING BY

REFERENCE

## **DECLARATION OF PRIOR INVENTION UNDER 37 C.F.R. § 1.131**

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Dear Sir/Madam:

This Declaration is submitted to establish prior invention of the subject matter of the present patent application. The persons making this Declaration are the inventors, Alan C. Berkema, Jeff Morgan, Pat Stoltz, and Todd Fischer.

Accompanying this Declaration are Exhibits A through E to establish conception of the subject matter of the present patent application in the United States prior to the earliest effective date of May 21, 2001 of the Nordman U.S. Patent Application Publication No. 2002/0174364 coupled with due diligence from a date prior to the earliest effective date of the Nordman Publication up to the filing date of the present patent application (i.e., constructive reduction to practice).

3 3

Declaration under 37 C.F.R. § 1.131

Applicant: Alan C. Berkema et al.

Serial No.: 09/897,656 Filed: June 29, 2001 Docket No.: 10016784-1

Title: PORTABLE WIRELESS DEVICE AND SOFTWARE FOR PRINTING BY REFERENCE

Exhibit A (33 pages) includes an HP Invention Disclosure prepared and submitted by inventors, Alan C. Berkema, Jeff Morgan, and Pat Stoltz, on May 1, 2001. This invention disclosure entitled "Portable Wireless Device and Device Software for Printing by Reference" describes subject matter of the present patent application, and was assigned HP Patent Disclosure Number ("PDNO") 10016784.

Exhibit B (1 page) includes an email dated May 16, 2001 from HP Patent Agent Dave Mason to inventor Alan C. Berkema providing a list of titles and associated HP ID numbers for patent applications to be prepared based on invention disclosures 10016066 ("Print By Reference") and 10016067 ("Printer Service Interface"). Included in this list is invention disclosure 10016784-1 ("Portable Wireless Device And Device Software For Printing By Reference") (i.e., the present patent application).

Exhibit C (1 page) includes a copy of a letter dated May 17, 2001 from HP Patent Agent David M. Mason to patent attorney Roger D. Greer of Greer, Burns & Crain requesting a quote of the cost to prepare a US patent application based on HP Invention Disclosure No. 10016784-1 (i.e., the present patent application).

Exhibit D (1 page) includes a Request for Quote and Engagement Letter Agreement for the preparation of a US patent application based on HP Docket No. 10016784 (i.e., the present patent application). The agreement was signed by patent attorney Roger D. Greer of Greer, Burns & Crain on May 21, 2001 and by HP Patent Agent David M. Mason on May 22, 2001.

Exhibit E (3 pages) includes an email string including a final email dated June 22, 2001 from patent attorney Steven P. Fallon of Greer, Burns & Crain to inventors Alan C. Berkema and Jeff Morgan forwarding a draft application based on related invention disclosure HP 10016067-1. The email also provides a list of the applications being prepared for the inventors. Included in this list is invention disclosure 10016784-1 ("Portable Wireless Device And Device Software For Printing By Reference") (i.e., the present patent application).

During the period between May 17, 2001 and June 29, 2001, the patent application for invention disclosure 10016784-1 (i.e., the present patent application) was prepared, and on June 29, 2001 the patent application for invention disclosure 10016784-1 (i.e., the present patent application) was filed.

Declaration under 37 C.F.R. § 1.131 Applicant: Alan C. Berkema et al.

Serial No.: 09/897,656 Filed: June 29, 2001 Docket No.: 10016784-1

Title: PORTABLE WIRELESS DEVICE AND SOFTWARE FOR PRINTING BY REFERENCE

From these exhibits, it can be seen that the subject matter of the present patent application was conceived in the United States prior to the earliest effective date of May 21, 2001 of the Nordman U.S. Patent Application Publication No. 2002/0174364 coupled with due diligence from a date prior to the earliest effective date of the Nordman Publication up to the filing date of the present patent application (i.e., constructive reduction to practice).

Name:	Alan C. Berkema	Date: 12/13/2006
Name:	Jeff Morgan	Date:
Name:	Pat Stoltz	Date:
Name:	Todd Fischer	Date:

Declaration under 37 C.F.R. § 1.131 Applicant: Alan C. Berkema et al.

Serial No.: 09/897,656 Filed: June 29, 2001 Docket No.: 10016784-1

Title: PORTABLE WIRELESS DEVICE AND SOFTWARE FOR PRINTING BY REFERENCE

From these exhibits, it can be seen that the subject matter of the present patent application was conceived in the United States prior to the earliest effective date of May 21, 2001 of the Nordman U.S. Patent Application Publication No. 2002/0174364 coupled with due diligence from a date prior to the earliest effective date of the Nordman Publication up to the filing date of the present patent application (i.e., constructive reduction to practice).

Name:	Date:
Alan C. Berkema	
Name: Jeff Morgan	Date: Dec 13 2006
Name:Pat Stoltz	Date:
Name:	Date:

Declaration under 37 C.F.R. § 1.131

Applicant: Alan C. Berkema et al.

Serial No.: 09/897,656 Filed: June 29, 2001 Docket No.: 10016784-1

Title: PORTABLE WIRELESS DEVICE AND SOFTWARE FOR PRINTING BY REFERENCE

From these exhibits, it can be seen that the subject matter of the present patent application was conceived in the United States prior to the earliest effective date of May 21, 2001 of the Nordman U.S. Patent Application Publication No. 2002/0174364 coupled with due diligence from a date prior to the earliest effective date of the Nordman Publication up to the filing date of the present patent application (i.e., constructive reduction to practice).

Name:		Date:
	Alan C. Berkema	·
Name:	Jeff Morgan	Date:
Name:	Pat Stoltz	Date: <u>DLC 14, 20</u> 06
Name:	Todd Fischer	Date:

Declaration under 37 C.F.R. § 1.131 Applicant: Alan C. Berkema et al.

Scrial No.: 09/897,656 Filed: June 29, 2001 Docket No.: 10016784-1

Title: PORTABLE WIRELESS DEVICE AND SOFTWARE FOR PRINTING BY REFERENCE

From these exhibits, it can be seen that the subject matter of the present patent application was conceived in the United States prior to the earliest effective date of May 21, 2001 of the Nordman U.S. Patent Application Publication No. 2002/0174364 coupled with due diligence from a date prior to the earliest effective date of the Nordman Publication up to the filing date of the present patent application (i.e., constructive reduction to practice).

Name:	Date:
Alan C. Berkema	,
Name:	Date:
Name:Pat Stoltz	Date:
Name: Lodd Fischer	Date: 0 6 11, 2006

Employee No. Name Entity & Lab Name

PACKARD INVENTION DISCLO	SURE		PAGE	
ONE OF		~ 1 0001		
PDNO 10016107	DATE RCVD	5. 200		
ONE OF	PS ROSEV	•		
Instructions: The information contained in this de	ocument is COMPANY CONFI	DENTIAL and may not be		
without prior authorization. Submit this disclosure			patent protection is	
possible until a patent application is authorized, pre Descriptive Title of Invention:				
PORTABLE WIRELESS DEVICE A	LUX DEVICE SIGN	ARE TO PRINTING	By PETALON	
Name of Project:	100 00000000000000000000000000000000000	1,1-0,10	Paria :	
Product Name or Number:				
Was a description of the invention published, or are	you planning to publish? If so	the date(s) and publication	(s): Submitted to	
the Bluetooth Printer Working Group and Associate			(-/. <u></u>	
Was a product including the invention announced, of	offered for sale, sold, or is such	activity proposed? If so, the	e date(s) and	
location(s): <u>June 2001</u>		. •		
Was the invention disclosed to anyone outside of H				
If any of the above situations will occur within 3 mor			115-857-2542	
Was the invention described in a lab book or other	record? If so, please identity (la	D DOOK #, etc.)		
		•		
Was the invention built or tested? If so, the date:				
	·			
Was this invention made under a government contr	ract? If so, the agency and cont	ract number: No.	· · · · · · · · · · · · · · · · · · ·	
THE WAS THE WAS THE COMMENT OF THE C	idot. Il bo, allo agorio, alla solit			
Description of Invention: Please preserve all rec			owing. Each	
	e signed and dated by the inven		alan natanta ata l	
A. Prior solutions and their disadvantages (i     B. Problems solved by the invention.	ir available, attach copies of pro-	nuct literature, technical ani	cies, paterits, etc.).	
C. Advantages of the invention over what ha	as been done before.		•	
D. Description of the construction and opera		propriate schematic, block,	& timing diagrams;	
drawings; samples; graphs; flowcharts; c	computer listings; test results; etc	2.)		
Signature of Inventor(s): Pursuant to my (our) e	mployment agreement, I (we) su	bmit this disclosure on this	date: [ 1999 ].	
	Signature		Mailstop	
Entity & Lab Name	Signature			
358399 Alan Berkema D366-6540 NPSD		785-5605	5558	
IIIS				
1	Classic	Talask	Mailatan	
Employee No. Name Entity & Lab Name	Signature	Teinet	Mailstop	
Employee No. Name	Signature	Telnet	Mailstop	
Entity & Lab Name		,		
1	•		*	

Signature

Telnet

Mailstop

Print By Reference Print Service Interface

Page 2 of 33

Employee No. Entity &	Name Lab Name	Signature	Telnet	Mailstop
Employee No. Entity &	Name Lab Name	Signature	Telnet	Mailstop
	(If more than six invente	ors, include additional information on another copy of this form	n and attach to this docu	ment)

PACKARD OF	INVENTION	DISCLOSURE	COMPANY CONFIDENTIAL	PAGE
		to obtain the signature of the person(s) and understood by, me (us) on the		]
Full Name Signature		Signature		Date of
Full Name Signature		Signature		Date of
Inventor & Hom	e Address Informat	ion: (If more than four inventors, Inclu	de addl. information on a copy of this form & att	ach to this document)
Inventor's Full Name Alan Chris Berke				
Street 8803 Quartzite C	ircle			
City Zip				State
Granite Bay 95746				California
Do you have a Resid Zip	lential P.O. Address? P.C	D. BOX	City	State
Greeted as (nicknam	ne, middle name, etc.)	Alan	Citizenship USA	
Inventor & Hom Inventor's Full Name Jeff Morgan		tion: (If more than four inventors, inclu	de addl. information on a copy of this form & at	tach to this document)
Street				
City Zip				State
Do you have a Resid Zip	dential P.O. Address? P.	O. BOX	City	State
Greeted as (nicknan	ne, middle name, etc.)	Jeff	Citizenship	7
Inventor & Hom	ne Address Informa	tion: (If more than four inventors, inclu	de addl. information on a copy of this form & at	tach to this document)
Inventor's Full Name Pat Stoltz	)	,		
Street				
City Zip				State
Do you have a Resid	dential P.O. Address? P.	O. BOX	City	State

Page 4 of 33

			•
Greeted as (nickname, middle name, etc.)	Alan	Citizenship	
Additional documen	tation		
Additional document			
			<del></del>
Invention description			
This invention provides a mechan	nism to		

Print By Reference Print Service Interface	Page 5 of 33	
<u></u>		
	•	

Prior solutions and their disadvantages (if available, attach copies of product literature, technical articles, patents, etc.).

Problems solved by the invention

Advantages of the invention over what has been done before

Description of the construction and operation of the invention (include appropriate schematic, block, & timing diagrams; drawings; samples; graphs; flowcharts; computer listings; test results; etc.)

### Abstract:

This document is a specification of the print-by-reference Print Service Interface. The Print Service Interface is the interface between the Printer and the Print Service. The Printer accesses the Print Service, via the Print Service Interface, when the Printer is carrying out a print-by-reference request. The Printer uses the Print Service to resolve and access the information to be printed. An extension to the Print Service Interface allows another device, like a mobile appliance, to provide a reference and a target Printer to the Print Service. HTTP based communication is used between the Printer and the Print Service.

## Introduction

The purpose of this document is to provide a specification of the Print By Reference Print Service Interface. This document should be read in conjunction with a document specifying a Print By Reference solution, such as the Bluetooth Printing Profile [BPP].

Throughout this document the Print Service is described from the Printer's point of view, as seen through the Print Service Interface. The Print Service may support other interfaces. The Print Service may also be a confederation of components all working together to provide the Print Service functionality. This specification does not limit the design or implementation of a Print Service beyond specifying the interface used by the Printer. The term client is used for a device which uses the Print Service, such as a Printer, Sender or other e-service.

### Scope

PBR is a print specific use of the more general Service by Reference model. The philosophy and guidelines supporting Service by Reference have been used in defining the Print Service Interface Jeff Morgan to describe this in general. For instance all SBR support three common methods in the API.

Figure 1 shows an example architecture that supports the Print By Reference model. Figure 1 is from the Bluetooth Printing Profile specification [BPP]. The B interface in Figure 1 is the primary scope of this document. This document will also specify extensions to the Print Service Interface to support the C interface. The other interfaces listed in Figure 1 are out of scope for this document.




Figure 1: Example Print by Reference System Architecture

## Key Interfaces

#### Print Service Interface (B)

The Printer to Print Service Interface (B), which is called the Print Service Interface in this document, is used by the Printer to communicate with a Print Service. The Print Service supports the functionality required to process the reference on behalf of the Printer. The core functionality of the Print Service includes; job control, accessing the information source and translation of information source to a form that can be used for printing. The Print Service Interface is required to support the deployment of multi-vendor-Print Services that are independent of the Printer type used.

#### Mobile Device to Print Service Interface (C)

This interface is used by the mobile device to access a remote Print Service directly. In terms of functionality this interface is similar to (B). This interface is not restricted to mobile devices. Any device or e-service may use the C interface invoke a Print by reference operation. To support general web access to the Print Service by a user, a

pure web based presentation interface [I] should be supported. The web interface can be used by those devices that support the use of web based mark up information; like HTML or WML, to display a user interface.

#### Content Provider Interface (D)

This interface is used by the Print Service to access content. This interface is implemented as a standard web based HTTP or HTTPS access. Devices that support WAP will use standard gateways to access the services as those running over HTTP(S). The implementation and features provided by a content provider are outside of the scope of this document although recommendations to support certain security modes are made within this document.

In addition to standard web acess we could support a web base imaging API or other indutry standard rich content API like HailStormMyDocuments.

#### Other Uses

Although tailored for supporting a PBR use model the PS can be used in other valuable ways.

PS invoked by the printer when the printer receives a print job directly in a format it does not support

Information services, like customized newspapers, can use PSs to handle the complexity of distributing and converting the information into an acceptable form for each Target printer.

The PS is useful whenever a solution distributing information needs to get the info in a form acceptable to the printer. If you need a driver just use the PS (not necessarily windows drivers)

## **Print Service Use Models**

A Print Service must be able to support a number of use models in order to serve the needs of a diverse set of clients. This section describes some possible use models, along with more detailed information about the nature of the Sender, Printer, and Print

Service interfaces required to support the use model. This should not be considered a complete list<sup>1</sup>.


The following table is part of the Bluetooth Print By Reference Marketing requirements document. It is included to illustrate the interactions with the Print Service Interface.

Use Model	Description	Reference Processed by	Pull/ Streaming	Interface	Priority Rating
1	Printer can consume format of reference target without a PS	Printer	Printer pulls content directly from Internet	A - Reference D - Print Data	2
2	Printer needs PS to print reference target	Printer	Printer pulls content via PS	A - Reference B - PS control and print data D - Content	1
3	Streaming of printer consumable data from CP to printer through appliance using BPP	Appliance	Appliance streams data over cellular network to printer	A – Print Data D - Print data	4
4	Streaming of print data from PS through appliance to printer using BPP	Appliance	Appliance streams data over cellular network to printer	A - Print data C - PS control and print data D - Content	3

The use models in the following sections focus on the reference and the data flow. The specification of the Print Service Interface shall also consider discovery, device capabilities, job control and status.


## Use Model 1

Printer can consume format of reference target without a PS. Interaction starts with the transfer of a reference from the Sender to the printer via the Bluetooth Print By Reference protocol (A). The reference refers to some information source in the network. A Print Service is not required to process the data. The printer can retrieve the data directly from the content provider.



#### Use Model 2


Printer needs PS to print reference target. Interaction starts with the transfer of a reference from the Sender to the printer via the Bluetooth Print By Reference protocol (A). The reference refers to some information source in the network. The reference will specify the address of the Print Service to use as well as other information relating to the access of the reference. Information on the reference formats used in Bluetooth Print By Reference can be found in Section 10.4 of [BPP]. The printer then uses the Print Service Interface to process the reference information before printing can commence (B). The Print Service must acquire information about the capabilities of the printer in order to process the request. This information or the means to obtain it is sent as part of the print request over the B interface. The Printer retrieves the converted data using the



B interface.


# Use Model 3

Streaming of printer consumable data from CP to printer through appliance using BPP. This use model is not illustrated since the Print Service Interface is not required.



# Use Model 4 (capabilities communication arrow?)

Streaming of print data from PS through appliance to printer using BPP. The sender sends the reference information to the Print Service using interface C. The Print Service retrieves the data using interface D. The Print Service must acquire information about the capabilities of the printer in order to process the request. This information or the means to obtain it is sent as part of the print request over the C interface. The Sender retrieves the converted data using the C interface. The print job is sent to the printer using the A interface.



# **Print Service Interface Requirements**

This section describes the general requirements of a Print Service Interface. These requirements will be based on the use models defined above along with the issues of Discovery, Print Job Control, Security and Billing.

Both PUSH and PULL data transport models are required to cross fire walls.

## Information Flow Requirements

The use models defined above can be supported with the following general requirements for the flow of information between the Printer or the Sender and the Print Service Interface

- 1. The Print Service must support the ability for a client (Printer or Sender) to upload information (PUSH) to the Print Service for Processing.
- 2. The Print Service must support the ability for a client to send it a reference as defined in section 10:4:of BPP]
- 3. The Print Service can make printer ready information available by returning a URL to the information that can be downloaded (PULLED) by the client.
  - 4. The Print Service can make printer ready information available by downloading (PUSHING) the information to the printer.
  - 5. The Print Service can optionally support a web interface, which can be used by suitably enabled clients to access a web based print service (.
  - 6. The Print Service can optionally support a Reflected UI, which can be used to request information from the user when a reflected UI interaction is possible.

### Discovery Requirements

A Print Service needs to be discovered or located before it can be used. There are a number of discovery models that can be used. A particular implementation or printing solution will make specific choices on how discovery should be done. The following provides a selection of options available. This should not be considered a complete list.

1. **Pre-configured**: The location of a Print Service may be pre-configured into a Printer or Sender via a configuration interface.

- 2. **Service Registry**: The Print Service can be registered into a service registry. Printers and Senders can use the registry to locate a Print Service based on some set of search constraints. Registry infrastructures such as UDDI can be utilized for this purpose. The scope and use of a registry is outside the scope of this document. Propose that UDDI is used for service discovery.
- 3. Local Network Discovery: A Print Service can be located via network discovery protocols. There are a number of protocols defined for IP based networks including SLP and SSDP. SSDP is used by UPNP based devices.
- 4. Reference Based Location: A Printer can discover which Print Service to use by processing a reference sent to it from a Sender. The XML Reference encoding defined in the Bluetooth Basic Print Profile (section 10.4 of BPP) supports the specification of a Print Service URL (the use\_service attribute) in the reference.

## Print Job Control

The Print Service must provide the means for a Printer or Sender to control, monitor and cancel a Print operation. This leads to the notion of a Print Job and requires an identification scheme (Job Identifier) to distinguish one print operation from another.

When a Printer or Sender initiates a Print request it must have the option of setting attributes that determine the outcome of the Print operation. The Print Service Interface must support a standard set of print options supported by all Print Services. Extensions to this set must also be supported to allow for evolution and support of differentiated vertical markets. The initiation of a Print operation will result in the creation of a Print Job and an associated Job Identifier. All subsequent Print control operations will require a Job Identifier to link operations to a particular Print Job. If the Print Service can include the job identifier as the state variable that the sender or printer returns as a result of selecting a hyper link included in the BU web markup.

A Print\*Service\*must\*have\*some\*understanding\*of.the.capabilities\*of.the\*Rarticular\*Printer (and it's configuration) in order to provide print ready information. The Print Service Interface must provide the means for this information to be obtained before the processing of a Print request can begin.

Once a Print Job is underway the Printerior Sender must be able to query the status of the Print Job or to Cancel the Print Job.

## Security

A Print Service may need to protect itself from unauthorized use. To support this need the Print Service Interface must provide a mechanism for the Print Service to discover the identity of the client device (Printer or Sender) in order to enforce access control.

When processing a reference a Print Service may be challenged to provide credentials in order to access the information to be printed. The Print Service may obtain access credentials in the following ways:

- 1. Access credentials may be included in the reference as described in the Bluetooth Basic Print Profile (section 10.4).
- 2. The Print Service may pass the challenge back to the client who must then re-submit the request with the correct security information included. The reflect UI mechanism is used to deliver the challenge to the Sender.
- 3. A Print Service may optionally support privacy through the encryption of the information that travels across the B and C interfaces. This encryption can be imposed at the link level (e.g. HTTPS, IPSec) and established at connection set-up. Since this level of security occurs at the link level it has no bearing on the functionality of the Interface. Another approach is to have the information encrypted above the link level. The XML Reference encoding defined in the Bluetooth Basic Print Profile (section 10.4) supports the specification of a decryption key (the key ??? attribute) in the reference.

#### Billing

Billing is a complex issue and one that cannot be fully addressed in this document. The Reflected UI and Web based access models provide a convenient mechanism to support billing. This is because they interface with the user and as such offer flexibility in providing an interface into a particular billing model.

There are no standard or widely used billing models that can be recommended at this time for use by a standard Print Service Interface. Defining a billing interface just for Printing would not satisfy the needs of users who may interact with many services. Therefore billing outside of the web access model is considered to occur out of band from the Print Service Interface. The notion of an opaque billing identifier is supported to allow for reference to the out of band billing transaction to be referenced during a Print operation. The XML Reference encoding defined in the Bluetooth Basic Print Profile (section 10.4) supports the specification of a billing code (the ??? attribute) in the reference.

## **Functional Overview**

The section provides a functional overview of the Print Service Interface and describes the operations provided by the interface. The following section go into more detail and provide a specification of the interface. Figure 2 shows the communication architecture for the Print Service Interface.




Figure 2 Print Service Protocols

The Print Service Interface is layered on top of HTTP (HTTPS for secure access). HTTP is used because it provides an efficient and ubiquitous transport mechanism. The Print Service Interface also uses SOAP, the Simple Object Access Protocol. SOAP is used to define three actions that are exported by the Print Service. These actions along with generic HTTP access (HTTP GET and POST) support the requirements for the Print Service. The SOAP actions are described in more detail below and are specified in the section XX.

## Data Types and Structures

This section defines format and acceptable values of the major data types and structures used in the SOAP actions of the Print Service Interface.

## Reference

The XML specification for a Reference is defined in the Bluetooth Basic Print Profile, section 10.4.2. This specification supports the representation of a network reference plus Meta information required to access that information including:

- Security credentials
- Cookies

### Access proxies

A reference must include a URI which can be used to access the information, all other information is optional.

PSI:Tuple

A Tuple is a structure that represents a name/value pair. The value is polymorphic accessor as defined in <u>section 5.3 of the SOAP specification</u>. This allows the type of the value to be specified at runtime via the xsi:type attribute, defined in section 2.6.1 of the XML Schema Part 1.

Here are some examples of PSI:Tuples for a float and string value

```
<PSI:Tuple>
        <Name>Width</Name>
        <Value xsi:type="xsd:float">4.67</Value>
</PSI:Tuple>
<PSI:Tuple>
        <Name>Description</Name>
       <Value xsi:type="xsd:string">Grommit for a mustard mill
</PSI:Tuple>
The schema for this type is defined as follows
<element name="Tuple" type="PSI:Tuple"/>
<complexType name="Tuple">
        <sequence minOccurs="1" maxOccurs="1">
               <element name="Name" type="xsd:string/>
               <element name="Value"/>
        </sequence>
</complexType>
PSI:JobOptions
```

JobOptions is an array of PSI:Tuples that can be used to support the specification of arbitrary options for a Print Job. These Job Options are extensions to the standard options supported as arguments to the CreatePSJob action defined below. Print vendors and consortiums that wish to specify extended job options are strongly advised to used XML namespaces to avoid option name clashes for their extended JobOptions.

```
The XML Schema for PSI:JobOptions is defined as follows <element name="JobOptions" type= ="SOAP-ENC:Array"/>
```

The following shows an example of a PSI:JobOption

Page 20 of 33

This is an array of PSI:Tuples that can be used to specify a list of arbitrary printer capabilities. This allows a printer to pass device information to a cooperating Print Service to aid with the process of rendering print ready information.

```
The XML Schema for PSI:Capabilities is: <element name="Capabilities" type="="SOAP-ENC:Array"/>
```

### CreatePSJob

A Printer or Sender initiates a print job using CreatePSJob action. This action provides the Print Service all of the information required to create a print job and to begin the processing of a print operation. The Print service must create a unique Job Identifier (*JobID*) that can be used in subsequent operations to identify the print Job. CreatePSJob supports both print by reference and information upload as a means of providing content to the Print Service. If the client is printing a reference then this is sent the *Reference* argument of action. If the client plans to upload information to the print service it does not specify a Reference argument in the action request. When the client indicates that it wants to upload the information to be printed the Print Service must include a *DataSink* URL in the CreatePSJob response. The client must then send the information to the Print Service using a separate HTTP POST operation to the *DataSink* URL. The Print Service also returns the *JobID* and a *PrintSrc* URL to client. The PrintSrc URL is used to retrieve the Print ready information once the Print Service has processed the original information.

The following arguments and results exchanged during a CreatePSJob action. The omission of any IN argument will default to a value defined by the Print Service.

ab also the ball resident of the second	
Time	Argumentiname Support
	ure in Client win Print
	Service
Sinno	JobName of Market M
	Description: The user-friendly name of
	the specified job.
Simo con	yJob©riginatingUserName
	Description: The name of the user that
	submitted the specified job. Either
	supplied by the client or by the security
	infrastructure, if any.
	mirasu ucture, ir any.
String - F	re Document Formatic Services Services SIN 50 Co
	Description: Specifies the document
	format of the current job as a mime
	media type and any applicable version.

No.	Description: Specifies the number of copies of the current job to be printed.
Side	Sides: N © Mr
	Description: Specifies how pages are to be imposed upon the sides of a selected medium for the current job. Values:
	one-sided
	two-sided-long-edge
	two-sided-short-edge
14	NumberUp:  Description: Indicates the number of print-stream pages to impose upon a single side of an instance of a selected
	medium for the current job. Examples:
	1 = One page per side.
	2 = Two pages per side.
	4 = Four pages per side.
String	Orientation Requested
	Description: Indicates the desired orientation for printed pages of the current job. Values:
	Portrait
	Landscape
	ReverseLandscape
	ReversePortrait
Strings to	MediaSize
	Description: Identifies the size of medium to be used for the current job. Refer to section Error!
	Reference source not found. for a list of Media Sizes.
String	PrintQuality:  Description: Specifies the print quality requested for the current job. Values:
	Draft
}	Normal
}	High
	Note: Because of the vendor dependencies in print quality metrics (DPI etc.); print quality descriptions are kept intentionally generic.
Siring	HIVPélatoype

	Description: Identifies the type of	
	medium to be used for the current	
	job. Refer to section Error!	
	Reference source not found, for a	
	list of Media Types.	
	S ExtendedJobOptions : INI 0 0	
	Description: Array of extended	
	options to be applied to the print	
	Job. This provides an extension to	
	the standard Job control arguments.	
Reference	<u>Reference</u> / as IN O ∠MPs	
	Description: Used to pass reference	
	information to the Print Service. The	
	reference includes information to	
	resolve to a piece of information on the network. If a reference is not	
	supplied then the Print Service	
	assumes that the client will upload	
	the information to be printed via the	
	DataSink URL	
String.	PrinterIDY O	
	Description: IEEE 1284-2000 Device	
	ID	
PSI Capabilu		
	Description: An array of printer	Proston >> PS
•	capabilities that can be used by the	11/2
	print service to process the request. The client may supply this	1 1 1 1 7 1 7
	information however the printer may	Prostan
	not be able to interpret the	
	information without prior knowledge	
	of semantics	
jo -	Billingide in the control of the con	
	Description: Opaque identifier for	1 4
	billing system obtained out of band.	au L
Kara a sa	ODIT M M	out =
	Description: Unique Job Identifier	
	created by the print service for this print	
	request. The Job Identifier must be used	
	on subsequent requests that refer to this	
	<u>Job</u>	
Sirto.	- <u>a PohinSmic .</u> γ	
	Description: URL to be used by the	2 3 miles (25 A 27)
	client to upload data to the service via a	
i	HTTP POST.	





Table 1 CreatePSJob Action Information

#### Status

The Status action is used to inquire on the current status of a print job. The status requires that the client have a valid JobID obtained from a previous CreatePSJob action. The Print Service can provide three pieces of information in response to a Status action request:

- A mandatory Integer status identifier indicating the status of the print job according to the values in Table 3.
- An optional textual status message that can be displayed on a front panel or other user interface.
- An optional progress indicator describing the completion percentage of the print job.

The following table lists the SOAP arguments and responses for a status request



<u>Description: Number between 0 and 100 that provides an estimate of the completion status of the Print job.</u>

Table 2 Status SOAP Action Information

The following Table lists the valid Integer status codes for this action


Status C	ode Reason D. S. S. S.
0 <b>x</b> 00	Processing completed Print document ready for downloads.
0x01	Working
0x02	Accessing content
0x03	Translating content
	[Think of any more?: add them here].

Table 3 Status Codes

### Cancel

The Cancel action is used to cancel a Print request immediately. This will inform the Print Service that it may stop processing a request and reclaim any resources it may have allocated. This action must provide a valid JobId obtained from a previous CreatePSJob request.

The following table lists the SOAP arguments used in this action



# **Operational Overview**

This section will discuss the operation and use of the Print Service Interface. There are two main uses of the Interface. The first use supports a print by reference model where a print service client sends a reference to the Print service. The second use is used when the content is uploaded from the print service client.

# Reference Printing

The following table shows an example of an interaction between a Print service client (Printer, mobile device, e-service) and a Print Service.

Client	Printservice ! What's happened
Glient-starts Print job by sending a GreatePSJob Sending a Greate	What I would be a second of the second of th
<pre>POST /PrintService HTTP/1.1 Host: www.printersrus.com Content-Type: text/xml; charset="utf-8"</pre>	Syntax
Content-Length: nnnn SOAPAction: [TBD]	- 54 <sup>x</sup>
<pre><soap-env:envelope <soap-env:body="" http:="" schemas.xmlso="" xmlns:soap-env="http://schemas.xmlsoap.org/s SOAP-ENV:encodingStyle="> <psi:createpsjob xmlns:psi="URI-TBD"> <printname>PrintThis</printname></psi:createpsjob></soap-env:envelope></pre>	pap.org/soap/encoding/"/>
<pre></pre>	RpbjpvcGVuIHN1c2FtZQ==" />
	Print Service receives request Defermines into a Print by reference Job the cause a Reference
⇔GreateRSJob Response	TOPE CARE THE CARE THE ACTION OF THE ACTION

Page 26 of 33

request. Printer information is obtained: from the Binter(B Specified HTTP/1.1 200 OK Content-Type: text/xml; charset="utf-8" Content-Length: nnnn <SOAP-ENV: Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" SOAP-ENV: encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"/> <SOAP-ENV: Body> <PSI:CreatePSJobResponse xmlns:PSI="URI-TBD"> <Jobin>567832</Jobin> <PrintSrc>http://www.printersrus.com/printengine?PrintJob=567832</Print Src> </PSI:CreatePSJobResponse> </SOAP-ENV:Body> </SOAP-ENV: Envelope> Client tries to access the print data using a HITTP Get on the PrintSrc url Print Service is still processing the Print job so it returns a HTTP 202 HTTP/1.1 202 OK (Accepted) status code. See section 10.2.3 of RFC 2616 Olient waits before: trying the request a econd time Print Service has HTTP 1.1 200 OK Content-Length=nnn completed processing Content-Type=xxx the reference and responds to the GET [Content information] request with the data Glienteproce information Print Service will cache the Job information

Apptax

including the Printable data for a time period determined by the Print Service implementation before deletion.

The interaction shown above described the printing of a reference. The reference was included in the initial CreatePSJob request. In this example CreatePSJob was the only SOAP action used. The next example will demonstrate content upload and the use of the Status action.

# Content Upload

The following table shows a printing example utilizing a content upload from the client to the Print Service.

Client		Print Service 24
CHECK CHECK		FILM SELVICE SE
CONTRACTOR AND ADDRESS OF THE PARTY.		
Client starts Printiob by		
sending a CreateRSJob as the	。 OreatePSJob⊜u	
action 16		
POST /PrintService HTTP/1.1		
Host: www.printersrus.com Content-Type: text/xml; cha	wast-flutf Of	
Content-Length: nnnn	irsec= utr-6	
SOAPAction: [TBD]		
<soap-env:envelope< th=""><th></th><th></th></soap-env:envelope<>		
xmlns:SOAP-ENV="http://sc		
<pre>SOAP-ENV:encodingscyle="n <soap-env:body></soap-env:body></pre>	rctp://schemas.xmis	soap.org/soap/encoding/"/>
<psi:createpsjob< th=""><th></th><th></th></psi:createpsjob<>		
xmlns:PSI="URI-TBD	)">	
	:This	
<copies>2<th></th><th>·</th></copies>		·
<pre><pre><pre><pre><pre><pre><pre><pre></pre></pre></pre></pre></pre></pre></pre></pre>	YYZZ	
<pre> </pre>		
		Print Service receives
		regresi Deleminės hat i
		inerglent needs (c)
	.≑GreateP\$Job	
		entingse type courage has
	:- Response	RankService allocates a
		- Iseggenologies a
		Pinde URLande
		JoaiaSink URL Sanosa

inellocht or eeroges ormalis entro entro send ine data. Princi intormation is obtained. from the PrinterID HTTP/1.1 200 OK Content-Type: text/xml; charset="utf-8" Content-Length: nnnn <SOAP-ENV: Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" SOAP-ENV: encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"/> <SOAP-ENV: Body> <PSI:CreatePSJobResponse xmlns:PSI="URI-TBD"> <JobID>567833</JobID> <printSrc>http://www.printersrus.com/printengine?PrintJob=567833</print</pre> Src> <DataSink>http://www.printersrus.com/printupload?PrintJob=567833</DataS</pre> ink> </PSI:CreatePSJobResponse> </SOAP-ENV:Body> </SOAP-ENV: Envelope> Client sends the Data to the print service using a HTTP:/POSTHO:/ihe DataSink@BL Print Service accepts the HTTP/1.1 200 OK content and starts to process the information

Client Sends a Status action to learn the progress of the operation

```
POST /PrintService HTTP/1.1
Host: www.printersrus.com
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
SOAPAction: [TBD]
<SOAP-ENV: Envelope
       xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
       SOAP-ENV: encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"/>
            <SOAP-ENV: Body>
                         <PSI:Status
                                xmlns: PSI="URI-TBD">
                                        <JobID>567833</JobID>
                          </PSI:Status>
            </SOAP-ENV: Body>
  </SOAP-ENV:Envelope>
                                                                                                                                                                                 Printer has completed
 HTTP/1-13/200 OK 32
Content Type text/smi
Content Length - nnnn
                                                                                                                                                                                 processing and sends an
                                                                                                                                                                                 Appropriate Response to
                                                                                                                                                                                 the Status action. 🕹
                             StatusID>0x00<//>
StatusID>0x00<//>
StatusMessage>Ready
                                  % CompletionPercentage>100
Comple
                 The North Properties of the No
   Client usesta HTTP GET SEED
to the PrintURL to obtain $\frac{P}{P}$
    the Print data
                                                                                                                                                                                    Print Service has
                                                                                            HTTP 1.1 200 OK
                                                                                                                                                                                   completed processing
                                                                                            Content-Length=nnn
                                                                                            Content-Type=xxx
                                                                                                                                                                                   the reference and
                                                                                                                                                                                    responds to the GET
                                                                                             [Content information]
                                                                                                                                                                                    request with the data
      Client proce
                                                                                                                                                                                    Print Service will cache
                                                                                                                                                                                    the Job information
```

including the Printable data for a time period determined by the Print Service implementation before deletion.

The example above shows the use of content upload and the Status action. The Status action can be used to provide more detailed feedback on the progress of a Print Service operation.

# Cancelling a Print Job

This example shows the use of the Cancel action to stop a Print Operations

s Client		(PrintService
	eatéPSJob⇒; -	
POST /PrintService HTTP/1.1 Host: www.printersrus.com Content-Type: text/xml; charset= Content-Length: nnnn SOAPAction: [TBD]	="utf-8"	
<pre><soap-env:envelope <soap-env:body="" http:="" xmlns:soap-env="http://schemas SOAP-ENV:encodingStyle="> <psi:createpsjob xmlns:psi="URI-TBD"> <printname>PrintThis <reference copies="" url="copies&gt;" www.ceference="">"copies&gt;"co</reference></printname></psi:createpsjob></soap-env:envelope></pre>	//schemas.xmlso  content.com/foo Basic QWxhZGF	pap.org/soap/encoding/"/> p.htm" cookie="
		Pilint-Service receives recrest-De ermines il is
	OrealeFS-lob Fesponse	a Print by reference los decause a Reference a puncional de Reference a puncional de Reference a puncional de Reference a los de Reference a los de References a los d

```
and States to to rocess the
                                                      eques: Paner
Incometion is obenned
                                                      tomine Princip
HTTP/1.1 200 OK
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
<SOAP-ENV: Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  SOAP-ENV: encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"/>
   <SOAP-ENV: Body>
       <PSI:CreatePSJobResponse xmlns:PSI="URI-TBD">
            <Jobin>567834</Jobin>
<PrintSrc>http://www.printersrus.com/printengine?PrintJob=567832</Print
Src>
        </PSI:CreatePSJobResponse>
   </SOAP-ENV:Body>
</SOAP-ENV: Envelope>
Client cancels the Print
Jobrusing the Cancel s
action
POST /PrintService HTTP/1.1
Host: www.printersrus.com
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
SOAPAction: [TBD]
<SOAP-ENV: Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  SOAP-ENV: encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"/>
   <SOAP-ENV: Body>
        <PSI:Cancel
          xmlns:PSI="URI-TBD">
            <JobID>567834</JobID>
        </PSI:Cancel>
    </SOAP-ENV:Body>
 </SOAP-ENV: Envelope>
                                                       Ringer receives carteel
                                                       and stops processing in
Job. The printerredains
all resources associated
                                                       With the Job Sends a
                                                       Response back to the
                                                       client
```

FW Bluetooth Print by Reference; HP 10016066-67; GBC 65483 et al.

From: MASON, DAVE (HP-Cupertino, ex1) Sent: Wednesday, May 16, 2001 5:33 PM To: BERKEMA, ALAN C (HP-Roseville, ex1)

Subject: FW: Bluetooth Print by Reference; HP 10016066-67; GBC 65483 et

al.

Hi Alan, for future reference, please find below a list of titles and associated HP ID numbers for patent applications that will filed by Steve Fallon of Greer, Burns & Crane as soon as possible. As you know, these patent applications are all based on the original invention disclosures entitled "Print by Reference" (10016066) and "Printer Service Interface" (10016067).

Thanks, David

- 1. PORTABLE WIRELESS DEVICE AND PRINT DEVICE PRINT BY REFERENCE PROTOCOL (10016066-1)
- 2. PRINT SERVICE AND PRINT DEVICE PROTOCOL SUPPORTING PORTABLE WIRELESS DEVICE PRINTING BY REFERENCE (10016067-1)
- 3. PRINT BY REFERENCE METHOD FOR PORTABLE WIRELESS DEVICES (10016783-1)
- 4. PORTABLE WIRELESS DEVICE AND DEVICE SOFTWARE FOR PRINTING BY REFERENCE (10016784-1)
- 5. PRINTING DEVICES AND DEVICE SOFTWARE FOR SUPPORTING PORTABLE WIRELESS DEVICE PRINTING BY REFERENCE (10016785-1)
- 6. PRINT SERVICE AND METHOD FOR PORTABLE WIRELESS DEVICE PRINTING BY REFERENCE (10016786-1)
- 7. PRINT BY REFERENCE COMMUNICATION METHODS FOR PORTABLE WIRELESS DEVICE PRINTING (10016787-1)



Howlett-Packard Company 19111 Pruneridge Avenue Mail Stop 44L18 Cupertino, CA 95014-0795 www.hp.com

5/17/01

David M. Mason Senior Patent Agent IP Section, Legal Department

408.447.4046 Tol 408.447.0854 Fax dave\_mason@hp.com May 17, 2001

Mr. Roger D. Greer Greer, Burns & Crain Ltd. 300 S. Wacker Drive 25th Floor Chicago, IL 60606

RE: Request for Quote

HP PDNO: 10016784-1

Title: Portable Wireless Device and Device Software for Printing

by Reference

Inventor(s): Alan C. Berkema

#### Dear Roger:

Please give us a quote of the cost to perform the services indicated on the attached *Request For Quote And Engagement Letter Agreement* (hereinafter "RFQ") form, for the above-identified matter, pursuant to Outside Counsel Procedures revised October 15, 1999, a copy of which you have received and reviewed. The quote should be based on your preparing and providing the requested services by the date for receipt by HP and/or the USPTO as indicated.

Your quote should be submitted on the enclosed RFQ form. If we accept your quote, we will return a fully executed copy of the Agreement to you for your records. The Agreement will not be binding on you or on HP until signed by HP's authorized representatives.

If the Agreement is not signed and returned to HP, any bills submitted by you cannot be paid.

Thank you for your assistance. If performing these services might involve a possible conflict of interest for your firm, you should advise us within one week of receipt of this letter.

Sincerely,

David M. Mason Senior Patent Agent

David M. Mason 1 04

DMM/ff

Enclosure(s)

MAY-21-2001 14:29 GREER, BURNS & CRAIN, LTD 312 360 9315 P.04/07

EXHIBIT D

RE: Hewlett-Packard Docket No. 10016784

USSN:

<b>V</b>	6 A 6 A 6		
•	est for a quote for the follov firmation of your quote for th	_	
	mindadit di you, quote foi ti	10 10	5-11 Y 10001
PREPARE		V	
X Application			File with USPTO
Response			Return to HP for filing
Other			
X YOUR FINISH	IED PRODUCT TO HP SHOU	LD IN	CLUDE ALL ITEMS ON THE ENCLOSED CHECKLIST.
HP REQUIRED DATES:			Date for Receipt by HP
	6/30/01 ASAP		Date to be Filed in PTO
ND Amount of I	Dammade da la la la desde da d		and a supply of
nr Attorneys or i	Record: (to be included on t	(Ve D	scieration)
Custon	ner Number 022879		
HP Primery Techn	nical Contact: Alen C.	Berke	ema, M/S 5558
Telephone No	.: (916) 786-6605	F	AX No.:
HP Entity:	lips		
Address:	8000 Foothills Blvd. Rosaville, CA 95747-573	1	
ADDITIONAL TER	IMS OR INSTRUCTIONS:		
	duct to HP should include th off except those marked"Na		ched CHECKLIST with all Items included in the final
TOTAL PRICE:			(including Formal drawings)
for Outside Cour	ms of this Agreement includ Isel revised NCTORFR 15, 11	ing th	ne additional terms above, pursuant to the HP Procedures copy of which I have received and reviewed. This
Agreement will r	ot be binding on either party	/ until	signed by an authorized representative of HP.
GREER, BURNS	& CRAIN LTD.		HEWLETT-PACKARD COMPANY
	)		7
(V			$\sqrt{1}$
Ву:	fun		By: Junto
Roger D.'Gre	ie!		David M. Mason
Detail:	SMINI		5/22/2/

Re-10/00 (ELA)

steve listl

From: Steven P. Fallon [sfallon@gbclaw.net]

Sent: Friday, June 22, 2001 1:01 PM

To: 'BERKEMA, ALAN C (HP-Roseville, ex1)'; Jeff Morgan (E-mail)
Cc: 'Roger Greer (E-mail)'; 'MASON, DAVE (HP-Cupertino, ex1)'
Subject: HP 10016067-1; GBC 65542; Print By Reference Service Protocol

Alan and Jeff.

This is the first draft of the print service protocol application. It shares much with the print service method application, so the read should be easy. The new material to the specification is associated with the tables. The FIGS are from the Service Method application, but are re-attached for convenience. The claims are all new.

We need to work hard to get all applications ready for filing next week. You have second drafts for most of the applications. You have this new one from me, and one following later today from Kim Jacklin for the PDA.

Here is the list of applications:

PORTABLE WIRELESS DEVICE AND PRINT DEVICE PRINT BY REFERENCE PROTOCOL (10016066-1) Steve

PRINT SERVICE AND PRINT DEVICE PROTOCOL SUPPORTING PORTABLE WIRELESS DEVICE PRINTING BY REFERENCE (10016067-1) Steve

PRINT BY REFERENCE METHOD FOR PORTABLE WIRELESS DEVICES (10016783-1) Kim PORTABLE WIRELESS DEVICE AND DEVICE SOFTWARE FOR PRINTING BY REFERENCE 3.

(10016784-1) Kim

PRINTING DEVICES AND DEVICE SOFTWARE FOR SUPPORTING PORTABLE WIRELESS DEVICE PRINTING BY REFERENCE (10016785-1) Tom

PRINT SERVICE AND METHOD FOR PORTABLE WIRELESS DEVICE PRINTING BY REFERENCE (10016786-1) Steve

PRINT BY REFERENCE COMMUNICATION METHODS FOR PORTABLE WIRELESS DEVICE PRINTING (10016787-1) Tom

I hope we can talk on Monday to make sure that we are getting finished.

Best Regards, Steve

Steven P. Fallon Greer, Burns & Crain, Ltd 300 S. Wacker Drive 25th Floor Chicago, IL 60606 Ph: (312)360-0080 Fax: (312)360-9315 Email sfallon@gbclaw.net

\*\*\*\*\*\*\*\*\* This electronic mail may contain information which is confidential or privileged and exempt from disclosure under applicable law. The information is intended to be for the use of the recipients named in this mail. If you are not an intended recipient, be aware that any disclosure, copying, distribution or use of the contents of this information is without authorization and is prohibited. If you receive this electronic mail in error, please notify us by return electronic mail and destroy this mail immediately. Thank you for your cooperation.

----Original Message----Steven P. Fallon [mailto:sfallon@gbclaw.net] From: Thursday, June 14, 2001 4:25 PM

Page 1

steve listl

'BERKEMA, ALAN C (HP-Roseville, ex1)' To:

cc: 'Roger Greer (E-mail)'; 'MASON, DAVE (HP-Cupertino, ex1)'

RE: HP 10016786-1; GBC 65546; Print By Reference Service Method Subject:

Jeff and Alan,

This is a final draft which takes into account Alan's previous comments (included below) on an initial draft. I have "tracked" the new material in word. Please note that FIG. 1 has been modified to account for a bluetooth or other connection to the print service.. I'm not sure whether Alan will have access to this since he is away, and look forward to Jeff's comments. Jeff can call/email or whatever will work best. Best regards, Steve

<< File: 10016786.DOC >> << File: FIG1.PPT >> << File: FIG3.PPT >> <</pre> File: FIG2.PPT >> << File: FIG4.PPT >>

Steven P. Fallon Greer, Burns & Crain, Ltd 300 S. Wacker Drive 25th Floor Chicago, IL 60606 Ph: (312)360-0080 Fax: (312)360-9315 Email sfallon@gbclaw.net

\*\*\*\*\*\*\*\* This electronic mail may contain information which is confidential or privileged and exempt from disclosure under applicable law. The information is intended to be for the use of the recipients named in this mail. If you are not an intended recipient, be aware that any disclosure, copying, distribution or use of the contents of this information is without authorization and is prohibited. If you receive this electronic mail in error, please notify us by return electronic mail and destroy this mail immediately. Thank you for your cooperation.

----Original Message----

From:

Sent:

BERKEMA, ALAN C (HP-Roseville, ex1) [mailto:alan\_berkema@hp.com] Friday, June 01, 2001 5:19 PM
'Steven P. Fallon'; BERKEMA, ALAN C (HP-Roseville, ex1)
Roger Greer (E-mail); MASON, DAVE (HP-Cupertino, ex1) To: Cc:

RE: HP 10016786-1; GBC 65546; Print By Reference Service Method Subject:

<< File: 10016786.doc >> Steve,

Great start. I have attached a doc with changes on, that provide comments and suggestions.

Now a question, In FIG 3 and related text we talk about SOAP. We also call for SOAP in Claim 8 and 28. While SOAP is today's preferred implementation I think this could evolve to other web protocols in the future. Even in the near term it could evolve to using WSDL (Web Based Description Language) in addition to or in place of SOAP. See http://www.w3.org/TR/wsdl for more than you want to know about WSDL. WSDL is sort of new and I don't know much about it (I need to learn soon...).
I have also asked Jeff Morgan to comment on this question. Dave any thoughts?

steve listl Thanks for all you effort on these disclosures, Alan

----Original Message---From: Steven P. Fallon [mailto:sfallon@gbclaw.net]
Sent: Wednesday, May 30, 2001 3:25 PM
To: Alan Berkema (E-mail)
Cc: Roger Greer (E-mail); Dave Mason (E-mail)
Subject: HP 10016787-1; GBC 65546; Print By Reference Service Method

Alan,

I'm enclosing a draft of the application for a service method to protect the print service. The application contemplates software, etc., executing the method of a remote or local print service for the print by reference. A separate one will follow for the print service interface, basically directed to the protocol.

I look forward to your comments.

Best Regards, Steve

Steven P. Fallon Greer, Burns & Crain, Ltd 300 S. Wacker Drive 25th Floor Chicago, IL 60606 Ph: (312)360-0080 Fax: (312)360-9315 Email sfallon@gbclaw.net

\*\*\*\*\*\*\*\*\*\* This electronic mail may contain information which is confidential or privileged and exempt from disclosure under applicable law. The information is intended to be for the use of the recipients named in this mail. If you are not an intended recipient, be aware that any disclosure, copying, distribution or use of the contents of this information is without authorization and is prohibited. If you receive this electronic mail in error, please notify us by return electronic mail and destroy this mail immediately. Thank you for your cooperation.